

AMP3115 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class AB linear GaAsFET hybrid design
 Instantaneous bandwidth
 Suitable for all single channel modulations standards
 Built-in protection circuits
 High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	24.0 - 28.0 GHz	
Power Output Psat	1 Watt Min	
Power Output @ P1dB	29 dBm Min	
Power Gain	30 dB Min	
Power Gain Flatness	4.0 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
Noise Figure	12 dB Max	
Harmonics	>20 dBc	At rated Pout
Non Harmonics Spurious	>60 dBc Min	
Operating Voltage	9 VDC Nom	
Current Consumption	2 Amp Typ	At rated Pout
Max Input Power	+3 dBm	Without damage
Load VSWR Protection	5 : 1	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +65 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	70 X 60 X 27 mm	Excluding Connectors
Weight	TBD	
RF Connectors In/Out	SMA K Type female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	N/C	Reserved
2	N/C	Reserved
3	CURRENT SENSOR	$I_D @ 20mV/100mA$ Typ
4	TEMP SENSOR	$V_T @ 10mV/°C + 500mV$ Typ
5	SHUTDOWN	TTL
6,7	VDD	9VDC
8,9	GND	Ground



AMP3115 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING