

MPA1081 SOLID STATE MID POWER AMPLIFIER

FEATURES

- Class AB GaAs linear design
- Small form factor, light weight
- Instantaneous ultra-wide bandwidth
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	1.0 - 18.0 GHz	
Power Output Psat	1 Watt Min	CW
Power Output P1dB GCP	0.5 Watt Min	CW
Small Signal Gain	30 dB Min	
Power Gain Flatness	4 dB p-p Max	
Input Return Loss	-10 dB Typ	
Harmonics	-20 dBc Max	At rated Pout
Noise Figure	6.0 dB Max	
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	12 VDC \pm 0.2V	
Current Consumption	0.9 Amp Max	At rated Pout
Input Power Protection	+5 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +70°C	
Storage Temperature	-40 to +85°C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	70 x 60 x 15 mm	Excluding connectors
Weight	300 gr.	
RF Connectors In/Out	Hi-Freq. SMA female	
DC Power	Feed Thru	
Cooling	External Heatsink	Forced air required

PIN ASSIGNMENT

Pin	Function	Description
1	DC Voltage	+12VDC
2	GND	GND

OUTLINE DRAWING

