



# PSSA-1G6G-50

## 50W CW SS Amplifier

### Solid State Power RF Amplifier

The PSSA-1G6G-50 is a Solid State 50W (CW) RF Amplifier which covers frequency range from 1.0GHz to 6.0GHz. This amplifier can achieve high efficiency operation with proven reliability as is designed with the robust engineering and employment of the most advanced devices and components. The amplifier comes with 1 year warranty.

Parameter	Specification
<b><u>Electrical</u></b>	
Frequency Range	1.0-6.0GHz
Output Power	50W CW, 20W P1dB
Gain @ rated power	47dB min.
Input /Output	50 ohms(VSWR 2.0:1)
Impedance	
RF Input / Output	Type N Female
Connectors	
Modulation	AM / FM / Pulse
Spurious	-50dBc
Harmonics	-20dBc Typical
Prime Power	115Vac or 220Vac +/-10%, 50/60 Hz, Single Phase, 3 wires
<b><u>Mechanical</u></b>	
Configuration	Racks mounts 19"W x 26.13"D x 8.75"H
Cooling System	Air cooled ,self contained
Shock	MIL-STD-810C, method 516.2
Vibration	MIL-STD-810C, method 514.2
Temperature	0° to 40°C
Non-operating temp	0° to 60°C
Humidity	95% without condensation
Altitude	5, 000 feet

THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



### **Features [Build-in]**

- VSWR Protection with Power Fold back when VSWR is greater than 3:1.
- RS 232 & Ethernet Remote Control.
- Gain Control.
- Leveling Control [ALC].
- Internal Pre-Amp.
- RF Input / Output Connectors on the Front Panel.
- Standby/RF\_ON, Elapsed Time Metering in hours.
- Color TFT Touch screen Display with Front Panel Controls and Indicators.

### **OPTIONS**

- |     |  |
|-----|--|
| 001 | VSWR Protection against any output mismatch greater than 6:1; will operate without damage or oscillation against any magnitude and phase of source and load impedance. |
| 002 | Alternate Prime Power (specify at time of order).  |
| 003 | Pin-Diode Pulse Modulation.  |
| 004 | Forward RF Sample Port Type N Female -50dBc nominal on the Front or Rear Panel.  |
| 005 | Reflected RF Sample Port Type N Female -50dBc nominal on the Front or Rear Panel.  |
| 006 | RF Input / Output Connectors on the Front /Rear Panel (Specify front or rear at time of order).  |
| 007 | Gain Equalizer.  |
| 008 | Input Power Limiter.   |
| 009 | RF Safety Interlock, type BNC Connector.   |
| 010 | Slides for Rack mount.   |

Distributed by

### **Reliant EMC LLC**

3311 Lewis Ave  
Signal Hill, CA 90755  
Tel.:(408)9165750

**E-Mail:** [contact@reliantemc.com](mailto:contact@reliantemc.com)  
**Web:**[www.reliantemc.com](http://www.reliantemc.com)

*THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.*