



PSSA-4G6G-30

30W CW SS Amplifier

Solid State Power RF Amplifier

The PSSA-4G6G-30 is a Solid State 30W (CW) @ RF Amplifier which covers frequency range from 4.0GHz to 6.0GHz. This amplifier can achieve high efficiency operation with proven reliability as is designed with the robust engineering and employment of the most advanced devices and components. The amplifier comes with 1 year warranty.

| Parameter | Specification |
|------------------------------|--|
| <u>Electrical</u> | |
| Frequency Range | 4.0-6.0 GHz |
| Output Power | 30W CW |
| Gain @ rated power | 47dB min. |
| Gain Adjustment | 0 to 20dB |
| Input /Output Impedance | 50 ohms(VSWR 2.0:1) |
| RF Input / Output Connectors | Type N Female |
| Modulation | AM / FM / Pulse |
| Spurious | -50dBc |
| Harmonics | -20dBc Typical |
| Prime Power | 115Vac or 220Vac +/-10%, 50/60 Hz, Single Phase, 3 wires |
| <u>Mechanical</u> | |
| Configuration | Racks mounts 19"W x 26.13"D x 7"H |
| Cooling System | Air cooled ,self contained |
| Shock | MIL-STD-810C, method 516.2 |
| Vibration | MIL-STD-810C, method 514.2 |
| Temperature | 0° to 40°C |
| Non-operating temp | -10° to 60°C |
| Humidity | 95% without condensation |
| Altitude | 5, 000 feet |

THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Features [Build-in]

| | |
|---|--|
| • | VSWR Protection with Power Fold back when VSWR is greater then 3:1. |
| • | RS 232 & Ethernet Remote Control. |
| • | Gain Control. |
| • | Leveling Control [ALC]. |
| • | Internal Pre-Amp. |
| • | RF Input / Output Connectors on the Front Panel. |
| • | Standby/RF_ON, Elapsed Time Metering in hours. |
| • | Forward/Reflected Power Indication simultaneously on Front Panel display |
| • | Color TFT Touch screen Display with Front Panel Controls and Indicators. |

OPTIONS

| | |
|-----|--|
| 001 | VSWR Protection against any output mismatch greater then 6:1; will operate without damage or oscillation against any magnitude and phase of source and load impedance. |
| 002 | Alternate Prime Power (specify at time of order). |
| 003 | Pin-Diode Pulse Modulation. |
| 004 | Forward RF Sample Port Type N Female -50dBc nominal on the Front or Rear Panel. |
| 005 | Reflected RF Sample Port Type N Female -50dBc nominal on the Front or Rear Panel. |
| 006 | RF Input / Output Connectors on the Front /Rear Panel (Specify front or rear at time of order). |
| 007 | Gain Equalizer. |
| 008 | Input Power Limiter. |
| 009 | RF Safety Interlock, type BNC Connector. |
| 010 | Slides for Rack mount. |

Distributed by

Reliant EMC LLC

3311 Lewis Ave
Signal Hill, CA 90755
Tel.:(408)9165750

E-Mail: contact@reliantemc.com

Web:www.reliantemc.com

THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.