



PSSA-4G6G-30

30W CW SS Amplifier

Solid State Power RF Amplifier

The PSSA-4G6G-30 is a Solid State 30W (CW) @ RF Amplifier which covers frequency range from 4.0GHz to 6.0GHz. This amplifier can achieve high efficiency operation with proven reliability as is designed with the robust engineering and employment of the most advanced devices and components. The amplifier comes with 1 year warranty.

Parameter	Specification
<u>Electrical</u>	
Frequency Range	4.0-6.0 GHz
Output Power	30W CW
Gain @ rated power	47dB min.
Gain Adjustment	0 to 20dB
Input /Output Impedance	50 ohms(VSWR 2.0:1)
RF Input / Output Connectors	Type N Female
Modulation	AM / FM / Pulse
Spurious	-50dBc
Harmonics	-20dBc Typical
Prime Power	115Vac or 220Vac +/-10%, 50/60 Hz, Single Phase, 3 wires
<u>Mechanical</u>	
Configuration	Racks mounts 19"W x 26.13"D x 7"H
Cooling System	Air cooled ,self contained
Shock	MIL-STD-810C, method 516.2
Vibration	MIL-STD-810C, method 514.2
Temperature	0° to 40°C
Non-operating temp	-10° to 60°C
Humidity	95% without condensation
Altitude	5, 000 feet

THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Features [Build-in]

•	VSWR Protection with Power Fold back when VSWR is greater then 3:1.
•	RS 232 & Ethernet Remote Control.
•	Gain Control.
•	Leveling Control [ALC].
•	Internal Pre-Amp.
•	RF Input / Output Connectors on the Front Panel.
•	Standby/RF_ON, Elapsed Time Metering in hours.
•	Forward/Reflected Power Indication simultaneously on Front Panel display
•	Color TFT Touch screen Display with Front Panel Controls and Indicators.

OPTIONS

001	VSWR Protection against any output mismatch greater then 6:1; will operate without damage or oscillation against any magnitude and phase of source and load impedance.
002	Alternate Prime Power (specify at time of order).
003	Pin-Diode Pulse Modulation.
004	Forward RF Sample Port Type N Female -50dBc nominal on the Front or Rear Panel.
005	Reflected RF Sample Port Type N Female -50dBc nominal on the Front or Rear Panel.
006	RF Input / Output Connectors on the Front /Rear Panel (Specify front or rear at time of order).
007	Gain Equalizer.
008	Input Power Limiter.
009	RF Safety Interlock, type BNC Connector.
010	Slides for Rack mount.

Distributed by

Reliant EMC LLC

3311 Lewis Ave
Signal Hill, CA 90755
Tel.:(408)9165750

E-Mail: contact@reliantemc.com

Web:www.reliantemc.com

THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.