model	The size (W×D×Hmm)	outside size (W×D×Hmm)	volume	Temperature range	Humidity range	Temperature and humidity precision		Heating time	Cooling time	voltage	(KW) power
SMC-80-CA	400×400×500	700×1220×1450	80L		10%~98%	±0.2°C	±1%	0°C~100°C /20min	25°C~0°C /20min	220V	4.0
	500×500×600	800×1320×1550	150L							220V	4.5
	500×600×750	800×1420×1700	225L							220V	5.5
	800×600×850	1100×1420×1800	408L							380V	6.2
	1000×800×1000	1300×1520×1900	800L							380V	7.5
	1000×1000×1000	1300×1700×1950	1000L							380V	8.0
SMC-150-CB	400×400×500	700×1220×1450	80L		10%~98%	±0.2°C	±1%	-20°C~100°C /20min	25°C~-20°C /30min	220V	4.8
	500×500×600	800×1320×1550	150L							220V	5.3
	500×600×750	800×1420×1700	225L							220V	5.8
	800×600×850	1100×1420×1800	408L							380V	6.6
	1000×800×1000	1300×1520×1900	800L							380V	8.5
	1000×1000×1000	1300×1700×1950	1000L							380V	10
SMC-225-CC	400×400×500	700×1220×1450	80L		10%~98%	±0.2°C	±1%	-40°C~100°C /30min	25°C~-40°C /50min	220V	5.3
	500×500×600	800×1320×1550	150L							220V	6.5
	500×600×750	800×1420×1700	225L							220V	7.5
	800×600×850	1100×1420×1800	408L							380V	8.8
	1000×800×1000	1300×1520×1900	800L							380V	11.5
	1000×1000×1000	1300×1700×1950	1000L							380V	12.8
SMC-408-CD	400×400×500	700×1220×1450	80L		10%~98%	±0.2°C	±1%	-70°C~100°C /40min	25°C~-70°C /70min	220V	6.5
	500×500×600	800×1320×1550	150L							220V	7.3
	500×600×750	800×1420×1700	225L							220V	8.5
	800×600×850	1100×1420×1800	408L							380V	11.6
	1000×800×1000	1300×1520×1900	800L							380V	13.5
	1000×1000×1000	1300×1700×1950	1000L							380V	15.5

Distributed by: Reliant EMC LLC, 3311 Lewis Ave, Signal Hill CA 90755, 408-916-5750, www.reliantemc.com