ACCREDITED SITE VALIDATION

We are the European market leader in accredited site validations. Due to intensive investigation, many of our results have been adopted in international standards (e.g. CISPR 16 series). The resulting know-how lead is applied in the course of the services for our customers.

Standard Validation Measurement:

- Shielding Effectiveness
- NSA
- Site VSWR
- Field Uniformity
- Absorber Lined Shielding Enclosure
- Ambient Noise
- Freespace VSWR Measurement
- Table Influence
- Reverberation Chamber

Test Sites have to be Calibrated Regularly

Test sites have to be calibrated regularly even if there have not been any changes in the construction. We offer service for the accredited calibration of EMC test sites. The aim is to provide the traceability of the EMC test site as required by ISO 17025 for accredited test houses.

REFERENCES

Among our worldwide customers there are manufacturers of EMC test facilities, operators of EMC test houses, research centers, universities and companies measuring the electromagnetic fields generated by mobile communication base stations.

- More than 800 performance evaluations and expert reports regarding radiated-emission and radiated susceptibility sites world-wide since 1990 for all major test site producers.
- More than 16,000 antennas and field sensors calibrations for EMC test laboratories in Europe.
- Antennas with measurement systems and test software operated by major chamber manufacturers and test labs world wide.

Accredited test house No. 312 and Accredited calibration laboratory No. 0612 according to EN ISO/IEC 17025 - reports and certificates accepted worldwide (ILAC)



CONTACT

Seibersdorf Labor GmbH Radio Frequency Engineering 2444 Seibersdorf, Austria T: +43 50550-2882 E: rf@seibersdorf-laboratories.at www.seibersdorf-laboratories.at/rf For more information please visit: Seibersdorf Laboratories



2018 0 /29012018 -

SERVICES & PRODUCTS RADIO FREQUENCY ENGINEERING



0

PRODUCTS & SERVICES

The activities of our business unit are based on long lasting scientific research works. The research output is in line with European and international standardisation works and is published at scientific conferences. For our products, the research output is the basis for a continuous development. The team of experts is specialised in:

- Calibration of antennas, field probes and other RF equipment used for the measurement of electromagnetic compatibility
- Validation of EMC measurement test sites
- Antennas for site validation
- Measurement systems

ACCREDITED CALIBRATION SERVICES

Our accreditation for calibration according to ISO 17025:

- Antennas
- Field Probes
- RF test equipment (LISN, current probes, comb generators, attenuators, cables etc.)
- Recognised world-wide in all EA and ILAC member states.

Our team of experts offers you:

- Services of an independent calibration laboratory
- · Short turnaround time and flexible scheduling
- Antenna calibration all the year round



ANTENNAS & MEASUREMENT EQUIPMENT

Precision Omnidirectional Dipole Antennas - POD 16 / POD 618

- · Compliant to CISPR 16-1-4 for site validation above 1 GHz
- · Conically shaped radiation elements covered by a RFtransparent radome
- · Excellent dipole-like radiation pattern up to 18 GHz
- Fully automated positioning unit (SPA and SPM) available

Precision Conical Dipole Antennas - PCD 3100 / PCD 8250

- Broadband antennas
- Compliant to CISPR 16-1-4 for site validation in fully anechoic rooms up to 1 GHz



RefRad X

- A battery operated comb generator as well as a field source
- LISN check from 10 kHz
- Increased dynamic range via FibreLink X
- A valuable tool for engineers ensuring the guality of radiated and conducted EMC and EMF measurements

CalStan 10.0

- A software tool for automation of radio frequency measurements such as NSA. sVSWR. Cable Loss etc.
- Supports more than 240 instruments
- Free demo software available: https://rf.seibersdorf-laboratories.at/support/demo-software



Precision Loop Antenna - PLA-R

- Compliant to CISPR 16-1-4 and standards for radiated emission testing, 9 kHz - 30 MHz
- Active antenna, battery powered, with low noise preamp and passive mode for strong signals
- · Saturation detection (waveform independent) that communicates with RE test software
- Antenna mounting and stand for easy change of orientation (x, y, z) included

Loop Antenna Set for Site Validations - PLA-Set

- Active battery powered transmit loop antenna PLA-T and active receive loop antenna PLA-R
- Designed for NSA testing 9 kHz 30 MHz up to 10 m distance (CISPR 16-1-4, internal draft)
- Antenna mounting and stand for easy change of orientation (x, y, z) and laser pointer for alignment included
- Shielding Effectiveness measurement with large dynamic range (EN50147-1, IEEE 299) and no need for additional power amplifier

Preamplifier - SVV

- Low noise amplifiers for site validation measurements: NSA, SVSWR, Ambient Noise, Shielding Effectiveness
- 2 Frequency ranges 10 MHz -1 GHz and 1 18 GHz
- Robust design with N connectors and power supply